



Mathematical
Institute

Netgen Meets Firedrake

P. E. FARRELL *, S. ZAMPINI †, U. ZERBINATI *

* *Mathematical Institute*
University of Oxford

† *Extreme Computing Research Center*
King Abdullah University of Science and Technology

Firedrake User Meeting, Exeter, 6th of January 2023



Oxford
Mathematics



Solving a Partial Differential Equation

When solving a partial differential equation the following macro steps can be identified:

- ▶ Geometrical modelling,
- ▶ Meshing,
- ▶ Discretising a PDE,
- ▶ Solving the linear or nonlinear system.

We aim to allow the Firedrake user to do all the steps above described in a single script.



Why NetGen?

NetGen is an advancing front 2D/3D-mesh generator, with many interesting features. Among the most important:

- ▶ Python wrapping (through pybind11),
- ▶ Multiple ways of describing the geometry to be meshed, i.e. its builtin **Constructive Solid Geometry (CSG)** and the **Open Cascade Technology (OCCT)** geometry kernel,
- ▶ Supports mesh refinement (also anisotropic mesh refinement).

Getting Started – Installing NetGen

Install NetGen using Firedrake scripts

```
python3 firedrake-install --netgen  
python3 firedrake-update --netgen
```

PETSc

If you are using an external PETSc installation, it should be updated to include commit 654059db.


NetGen

If installing from scratch, use the NetGen fork from the Firedrake project GitHub.

Getting Started – Unstructured Mesh

```
1 from firedrake import *
2 from mpi4py import MPI
3 from netgen.geom2d import SplineGeometry
4 import netgen
5 comm = MPI.COMM_WORLD
6 if comm.rank == 0:
7     geo = SplineGeometry()
8     geo.AddRectangle((0, 0), (pi, pi), bc="rect")
9     ngmesh = geo.GenerateMesh(maxh=0.1)
10    labels = ngmesh.GetBCIDs("rect")
11 else:
12     ngmesh = netgen.libngpy._meshing.Mesh(2)
13     labels = None
14 labels = comm.bcast(labels, root=0)
15 msh = Mesh(ngmesh)
16 File("VTK/Poisson2DMesh.pvd").write(msh)
```


Getting Started – Unstructured Mesh



Getting Started – CSG 2D

```
1 from firedrake import *
2 from netgen.geom2d import SplineGeometry
3 geo = SplineGeometry()
4 geo.AddRectangle(p1=(-1,-1),p2=(1,1),bc="rectangle",
5     leftdomain=1,rightdomain=0)
6 geo.AddCircle(c=(0,0),r=0.5,bc="circle",
7     leftdomain=2,rightdomain=1)
8 geo.SetMaterial(1, "outer")
9 geo.SetMaterial(2, "inner")
10 geo.SetDomainMaxH(2, 0.05)
11 ngmesh = geo.GenerateMesh(maxh=0.2)
12 msh = Mesh(ngmesh)
13 File("VTK/CSG2DMesh.pvd").write(msh)
```

Getting Started – CSG 2D




Material Identifiers

The material identifier specified above are carried to the DMPLEX as CELL_SETS_LABEL.

Getting Started – CSG 3D

```
1 from firedrake import *
2 from netgen.csg import *
3 geo = CSGeometry()
4 brick = OrthoBrick(Pnt(-1,-1,-1),Pnt
                     (1,1,1))
5 sphere = Sphere(Pnt(0.5,0.5,0.5),1)
6 sphere.maxh(0.05)
7 geo.Add(brick-sphere)
8 ngmesh = geo.GenerateMesh(maxh=0.3)
9 msh = Mesh(ngmesh)
10 File("VTK/CSG3DMesh.pvd").write(msh)
```



Getting Started – CSG Surfaces

```
1 from firedrake import *
2 from netgen.csg import *
3 from netgen.meshing import
    MeshingParameters
4 from netgen.meshing import
    MeshingStep
5 from irksome import
    GaussLegendre, Dt,
    TimeStepper
6 geo = CSGeometry()
7 geo.Add(Sphere(Pnt(0,0,0),1).bc(
    "sphere"))
8 mp = MeshingParameters(maxh=0.1,
    perfstepsend = MeshingStep.
    MESH_SURFACE)
9 ngmesh = geo.GenerateMesh(mp=mp)
10 msh = Mesh(ngmesh)
```


The Open Cascade Technology Kernel

- ▶ Basic OCCT objects can be used in NetGen such as: Box, Cylinder, Point, Segment and ArcOfCircle.
- ▶ The fuse, cut and common operations between OCCT objects have been wrapped in NetGen.
- ▶ Transformation operations such as Move and Rotate have also been wrapped into NetGen.

The Open Cascade Technology Kernel


```
1 from firedrake import *
2 from netgen.occ import *
3 box = Box(Pnt(0,0,0), Pnt(1,1,1))
4 cyl = Cylinder(Pnt(1,0.5,0.5), X, r=0.3, h=0.5)
5 solid1 = box + cyl
6 solid2 = solid1.Rotate(Axis((0,0,0), Y), 180).Move
    ((2.5,0.,1.))
7 solid = solid2 + solid1
8 geo = OCCGeometry(solid)
9 ngmesh = geo.GenerateMesh(maxh=0.1)
10 msh = Mesh(ngmesh)
11 File("VTK/OCC.pvd").write(msh)
```

The Open Cascade Technology Kernel




The OCCT Kernel – The Flask Example: I

```
1 from firedrake import *
2 from netgen.occ import *
3 H, W, T = 70., 50., 30.
4 P1, P2=Pnt(-W/2, 0, 0), Pnt(-W/2, -T/4, 0)
5 P3, P4=Pnt(0, -T/2., 0), Pnt(W/2., -T/ 4., 0)
6 P5=Pnt(W/2., 0, 0)
7 S1=Segment(P1, P2)
8 A=ArcOfCircle(P2, P3, P4)
9 S2=Segment(P4, P5)
10 wire=Wire([S1, A, S2])
11 mwire=wire.Mirror(Axis((0,0,0), X))
12 wire=Wire([wire, mwire])
13 base=Face(wire).Extrude(0.3*Z)
14 msh=Mesh(OCCGeometry(base).GenerateMesh(
    maxh=0.5))
15 File("VTK/OCCBottleBase.pvd").write(msh)
```



The OCCT Kernel – The Flask Example: II

```
1 f = Face(wire)
2 f.bc("bottom")
3 body=f.Extrude(H*Z)
4 body=body.MakeFillet(body.edges,T
    /12)
5 neckAx=Axes(body.faces.Max(Z).center,Z)
6 NeckR,NeckH=T/4,H/10
7 neck=Cylinder(neckAx,NeckR,NeckH)
8 body=body+neck
9 fmax=body.faces.Max(Z)
10 thickbody=body.MakeThickSolid([fmax
    ],-T/50,1.e-3)
11 msh=Mesh(OCCGeometry(thickbody).
    GenerateMesh(maxh=3.))
12 File("VTK/OCCBottleBody.pvd").write
    (msh)
```






The OCCT Kernel – Linear Elasticity: I

```
1 from firedrake import *
2 from netgen.occ import *
3 box = Box((0,0,0), (3,0.6,1))
4 cyl = sum( [Cylinder((0.5+i,0,0.5), Y, 0.25,0.8) for i
    in range(3)] )
5 box.faces.name,cyl.faces.name="outer","cyl"
6 geo = box-cyl
7 cylboxedges = geo.faces["outer"].edges * geo.faces["cyl"].edges
8 cylboxedges.name = "cylbox"
9 geo = geo.MakeChamfer(cylboxedges, 0.03)
10 geo.faces.Min(X).name = "fix"
11 geo.faces.Max(X).name = "force"
12 ngmesh = OCCGeometry(geo).GenerateMesh(maxh=0.1)
13 msh = Mesh(ngmesh)
14 File("VTK/OCCSolidMesh.pvd").write(msh)
```

The OCCT Kernel – Linear Elasticity: II

```
1 V = VectorFunctionSpace(msh, "CG", 3)
2 W = FunctionSpace(msh, "CG", 3)
3 u,v = TrialFunction(V), TestFunction(W)
4 sol = Function(V)
5 lbFix = ngmesh.GetBCIDs("fix")
6 lbF = ngmesh.GetBCIDs("force")[0]
7 bc = DirichletBC(V, 0, lbFix)
8 f = as_vector([1e-3, 0, 0])
9 E, nu, Id = 210., 0.3, Identity(3)
10 mu = Constant((0.5/(1+nu))*E)
11 lambda_ = Constant(E*(nu/((1+nu)*(1-2*nu))))
12 epsilon = lambda_*grad(u) + grad(u).T
13 sigma = lambda_*div(u)*Id + 2*mu*epsilon(u)
14 a = inner(sigma(u), epsilon(v))*dx
15 L = inner(f, v)*ds(lbF)
```

The OCCT Kernel – Linear Elasticity: III



The OCCT Kernel – Multigrid: I


```
1 from firedrake import *
2 from netgen.occ import *
3 cyl = Cylinder((0,0,0), Z, r=0.01, h=0.03).faces[0]
4 heli = Edge(Segment((0,0), (12*pi, 0.03)), cyl)
5 ps,vs = heli.start, heli.start_tangent
6 pe,ve = heli.end, heli.end_tangent
7 e1 = Segment((0,0,-0.03), (0,0,-0.01))
8 c1 = BezierCurve( [(0,0,-0.01), (0,0,0), ps-vs, ps])
9 e2 = Segment((0,0,0.04), (0,0,0.06))
10 c2 = BezierCurve( [pe, pe+ve, (0,0,0.03), (0,0,0.04)])
11 spiral = Wire([e1, c1, heli, c2, e2])
12 circ = Face(Wire([Circle((0,0,-0.03), Z, 0.001)]))
13 coil = Pipe(spiral, circ)
14 coil.faces.maxh, coil.faces.name = 0.1, "coilbnd"
15 coil.faces.Max(Z).name, coil.faces.Min(Z).name = "I", "O"
16 ngmsh = OCCGeometry(coil).GenerateMesh(maxh=0.3)
```

The OCCT Kernel – Multigrid: II

```


1 msh = Mesh(ngmsh)
2 hierarchy = MeshHierarchy(msh, 2)
3 V = FunctionSpace(hierarchy[-1], "CG", 1)
4 u,v = TrialFunction(V), TestFunction(V)
5 a,L = dot(grad(u), grad(v))*dx, 1*v*dx
6 bcsI=DirichletBC(V,1,ngmsh.GetBCIDs("I"))
7 bcs0=DirichletBC(V,0.,ngmsh.GetBCIDs("0"))
8 u = Function(V)
9 parameters = {"ksp_type": "preonly", "
    pc_type": "mg",
10   "pc_mg_type": "full", "
    mg_levels_ksp_type": "chebyshev",
11   "mg_levels_ksp_max_it": 2,
    mg_levels_pc_type": "jacobi"}
12 solve(a==L, u, bcs=[bcsI, bcs0],
        solver_parameters=par)

```



Mesh Refinement – Adaptive Mesh Refinement: I

```
1 tolerance = 1e-16
2 max_iterations = 15
3 exact = 3.375610652693620492628**2
4 geo=SplineGeometry()
5 pnts=[(0, 0), (1, 0), (1, 1),(0, 1),
6      (-1, 1), (-1, 0),(-1, -1), (0, -1)]
7 P = [geo.AppendPoint(*pnt) for pnt in
     pnts]
8 L,B=[ "line", "spline3"],[ "line", "curve"]
9 curves = [[[L[0],P[0],P[1]],B[0]],
10           [[L[1],P[1],P[2],P[3]],B[1]],
11           [[L[1],P[3],P[4],P[5]],B[1]],
12           [[L[1],P[5],P[6],P[7]],B[1]],
13           [[L[0],P[7],P[0]],B[0]]]
14 [geo.Append(c, bc=bc) for c, bc in
    curves]
```





Mesh Refinement – Adaptive Mesh Refinement: II

```

1 if comm.rank == 0:
2     ngmsh = geo.GenerateMesh(maxh=0.2)
3     labels=sum([ngmsh.GetBCIDs(label)
4                 for label in ["line","curve"]], [])
5 else:
6     ngmsh=netgen.libngpy._meshing.Mesh
7     (2)
8     labels = None
9 msh = Mesh(ngmsh)
10 labels = comm.bcast(labels, root=0)
11 for i in range(max_iterations):
12     lam, uh, V = Solve(msh,labels)
13     mark = Mark(msh, uh, lam)
14     msh = msh.Refine(mark)
15     File("VTK/PacManAdp.pvd").write(uh,
16         mark)
17
18 assert(abs(lam-exact)<1e-2)

```



Conclusion

- ▶ Mesh **hierarchy awareness**, using Firedrake HierarchyBase class.
- ▶ Make the implementation works in **complex** arithmetic.
- ▶ Support for **anisotropic** mesh refinement, using NetGen ZRefinement and HPRefinement methods.
- ▶ Support for NetGen **high order** mesh in Firedrake.
- ▶ Support for MFEM **GLVIS** mesh and solution live display, thanks to PETSc-GLVIS interface.

Temporary page!

\LaTeX was unable to guess the total number of pages correctly. As there was some unprocessed data that should have been added before the final page this extra page has been added to receive it. If you rerun the document (without altering it) this surplus page will go away, because \LaTeX now knows how many pages to expect for this document.